

CJX2N Mechanical Interlocking Contactor



1. Specifications

Type	Electrical life (10000 times)	Rated current(A)	
		220V-380V	500V-600V
CJX2N-D09(LC2-D09)	20	3.5	1.5
CJX2N-D12(LC2-D12)	20	5	2
CJX2N-D18(LC2-D18)	20	7.7	3.8
CJX2N-D25(LC2-D25)	20	8.5	4.4
CJX2N-D32(LC2-D32)	20	12	7.5
CJX2N-D40(LC2-D40)	15	18.5	9
CJX2N-D50(LC2-D50)	15	24	12
CJX2N-D63(LC2-D63)	15	28	14
CJX2N-D80(LC2-D80)	10	37	17.3
CJX2N-D95(LC2-D95)	10	44	21.3

Type:CJX2N-F			115		1154		185		1854		265		2654		400		4004		500		630	
Maximum rated voltage			1000V		1000V		1000V		1000V		1000V		1000V		1000V		1000V		1000V		1000V	
Maximum thermal current 1th			200A		200A		270A		270A		350A		350A		500A		500A		700A		1000A	
Maximum rated current LL:Long life NL:Normal life 3phase 440V 50/60Hz			—	NL 120A	LL 115A	NL 150A	—	NL 185A	LL 185A	NL 205A	—	NL 265A	LL 265A	NL 300A	—	NL 400A	LL 400A	NL 450A	LL 500A	NL 630A	LL 630A	NL 1000A
Maximum standard power rating under AC3 duty	220V	kw hp	—	30 40	30 40	45 60	—	55 75	55 75	63 85	—	75 100	75 100	90 125	—	110 150	110 150	132 180	147 200	185 250	200 270	220 300
	380V	kw hp	—	55 75	55 75	75 100	—	90 125	90 125	110 150	—	132 180	132 180	160 220	—	200 270	200 270	220 300	250 340	335 450	335 450	400 540
	415/ 440V	kw hp	—	60 80	60 80	80 110	—	100 135	100 135	110 150	—	140 190	140 190	160 220	—	220 300	220 300	250 340	280 380	355 480	375 500	450 610