

LFH-A Floor Standing Industrial Enclosures



1. General

Monobloc floor standing enclosure made from a continuous length of sheet steel triple folded with back plate welded onto a flanged rear profile for higher protection. Painted with polyester epoxy powder paint to light grey RAL-7032 and texturized finish.

- New series LFH-A...GD with templated glass transparent door to IP-55
- Mounting plate with reinforced edges adjustable in depth.
- Reinforcement profile on plain doors with $\varnothing 4,25$ mm fixing holes every 25 mm
- Enclosure can be turned upside down for a cable entry from the top.
- Reversible door with 125° opening in all cases.

2. Specifications

External dimensions(mm)			Type			No.of doors	No.of hinges
Height (A)	Width (B)	Depth (C)	Enclosure without mounting plate	Enclosure with mounting plate	Enclosure with transparent door		
1000	1000	300	LFH-A 1010/30	LFH-A 1010/30MP	LFH-A 1010/30TD	2	4
1200	800	300	LFH-A 128/30	LFH-A 128/30MP	LFH-A 128/30TD	1	2
1200	1000	300	LFH-A 1210/30	LFH-A 1210/30MP	LFH-A 1210/30TD	2	4
1200	1200	400	LFH-A 1212/40	LFH-A 1212/40MP	-	2	4
1400	800	400	LFH-A 148/40	LFH-A 148/40MP	LFH-A 148/40TD	1	3
1600	800	300	LFH-A 168/30	LFH-A 168/30MP	LFH-A 168/30TD	1	3
1600	800	400	LFH-A 168/40	LFH-A 168/40MP	LFH-A 168/40TD	1	3
1600	1000	300	LFH-A 1610/30	LFH-A 1610/30MP	LFH-A 1610/30TD	2	6
1600	1000	400	LFH-A 1610/40	LFH-A 1610/40MP	LFH-A 1610/40TD	2	6
1600	1000	400	LFH-A 1610/40SB	LFH-A 1610/40SBMP	-	2	4+2
1600	1200	300	LFH-A 1612/30	LFH-A 1612/30MP	-	2	6
1600	1200	400	LFH-A 1612/40	LFH-A 1612/40MP	-	2	6
1800	800	400	LFH-A 188/40	LFH-A 188/40MP	LFH-A 188/40TD	1	3
1800	1200	400	LFH-A 1812/40	LFH-A 1812/40MP	-	2	6
1800	1200	400	LFH-A 1812/40SB	LFH-A 1812/40SBMP	-	2	6
1800	1600	400	LFH-A 1816/40	LFH-A 1816/40MP	-	2	4+2
2000	800	400	LFH-A 208/40	LFH-A 208/40MP	LFH-A 208/40TD	1	3
2000	1000	400	LFH-A 2010/40	LFH-A 2010/40MP	LFH-A 2010/40TD	2	6
2000	1200	400	LFH-A 2012/40	LFH-A 2012/40MP	-	2	6