

Cooling Fan



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
80×80×25	LF8025-1	115	50	0.14	15	2300	21	0.11	22	225
	LF8025-2	115	60	0.13	11	2800	23	0.15	24	225
	LF8025-3	230	50	0.08	16	2300	21	0.11	22	225
	LF8025-4	230	60	0.07	11	2800	23	0.15	24	225



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
92 × 92 × 25	LF9225-1	115	50	0.14	15	2300	25	0.13	23	270
	LF9225-2	115	60	0.13	12	2500	27	0.14	24	270
	LF9225-3	230	50	0.08	16	2300	25	0.13	23	270
	LF9225-4	230	60	0.07	11	2700	27	0.14	24	270



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
110×110×25	LF11025-1	115	50	0.16	17	2100	47	0.13	31	310
	LF11025-2	115	60	0.15	22	2400	52	0.14	34	310
	LF11025-3	230	50	0.10	18	2100	47	0.13	31	310
	LF11025-4	230	60	0.09	22	2400	52	0.14	34	310



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
120 × 120 × 25	LF12025-1	115	50	0.16	17	1800	49	0.14	36	320
	LF12025-2	115	50	0.23	24	2100	61	0.13	38	320
	LF12025-3	115	60	0.19	19.70	2400	70	0.15	44	320
	LF12025-4	230	50	0.10	18	1800	49	0.14	36	320
	LF12025-5	230	50	0.11	21	2100	61	0.13	38	320
	LF12025-6	230	50	0.10	18	2400	70	0.15	44	320



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
120 × 120 × 38	LF12038-1	115	50	0.25	25	2500	87	0.23	46.5	510
	LF12038-2	115	60	0.23	20	2900	108	0.28	52.6	510
	LF12038-3	230	50	0.14	25	2500	87	0.23	46.5	510
	LF12038-4	230	60	0.12	20	2900	108	0.28	52.6	510
	LF12038-5	380	50	0.14	25	2500	87	0.23	46.5	510
	LF12038-6	380	60	0.12	20	2900	108	0.28	52.6	510

Cooling Fan



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
135 × 135 × 32	LF13532-1	115	50	0.28	25	2350	92	0.29	44.3	510
	LF13532-2	230	50	0.16	25	2350	92	0.29	44.3	510
	LF13532-3	380	50	0.12	30	2300	92	0.29	44.3	510



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
172 × 152 × 39	LF15239-1	110	50	0.30	35	2400	4.1	22	Ci21 3UF250V	700
	LF15239-2	220	50	0.13	27	2400	4.1	22	CBB22 IUF/400V	700
	LF15239-3	220	50	0.15	30	2600	4.6	24	CBB22 IUF/400F	700
	LF15239-4	380	50	0.10	26	2400	4.1	22	CBB21 334J630V	700
	LF15239-5	380	50	0.12	30	2600	4.6	24	CBB21 344J630V	700



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
152 × 172 × 51	LF17251-1	115	50	0.33	25	2500	180	0.38	49.6	900
	LF17251-2	115	60	0.30	23	2700	195	0.52	53	900
	LF17251-3	230	50	0.18	25	2500	180	0.38	49.6	900
	LF17251-4	230	60	0.25	40	2900	195	0.52	53	900
	LF17251-5	380	50	0.14	30	2600	180	0.38	49.6	900



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
152 × 172 × 52	LF17252-1	115	50	0.33	25	2500	180	0.38	49.6	900
	LF17252-2	115	60	0.30	23	2700	195	0.52	53	900
	LF17252-3	230	50	0.18	25	2500	180	0.38	49.6	900
	LF17252-4	230	60	0.25	40	2900	195	0.52	53	900
	LF17252-5	380	50	0.14	30	2600	180	0.38	49.6	900



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
180 × 180 × 61	LF18061-1	115	50	0.60	50	2500	255	0.60	58	1700
	LF18061-2	230	50	0.35	55	2500	255	0.60	58	1700
	LF18061-3	380	50	0.25	60	2500	255	0.60	58	1700



Technical parameter

Dimension (mm)	Type	Voltage (VAC)	Frequency (Hz)	Current (AMP)	Power (Watts)	Speed (RPM)	Air Flo (CFM)	Pressure (Inch/HO)	Moise (dBA)	Weight (Gram)
200 × 200 × 61	LF20061-1	115	50	0.80	65	2300	254	0.58	56	1800
	LF20061-2	230	50	0.45	70	2500	285	0.65	60	1800
	LF20061-3	380	50	0.28	70	2500	285	0.65	60	1800