

NT H. R. C Low Voltage Fuse



1. General

- 1.1 NT low voltage H. R. C. Fuse has features of light in weight, small in size, low in power loss and high in breaking capacity.
- This product has been widely used in overload and short circuit protection of electric installation.
- 1.2 This product conforms to IEC 269 standards with all of the rating at the world advanced level.
- 1.3 Rated breaking capacity:
- 500V-120KA, 660V-50KA

2. Specifications

Fuse link					Fuse base		
Type	Rated current (A)	Rated voltage (V)	Rated power loss(W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT00C	2	500, 600	0.41	0.15	Sist 101	160	0.2
	4		0.62				
	6		0.81				
	10		1.08				
	16		1.60				
	20		1.81				
	25		2.31				
	32		3.07				
	36		3.17				
	40		4.05				
	50		4.25				
	63		4.70				
	80		5.7				
	100		7				

NT H. R. C Low Voltage Fuse

Fuse link					Fuse base		
Type	Rated current(A)	Rated voltage(V)	Rated power loss(W)	Weight (kg)	Type	Rated current(A)	Weight (kg)
NT00	4	500,600	40.67	0.15	Sist 160	160	0.2
	6	500,600	0.89				
	10	500,600	1.14				
	16	500,600	1.65				
	20	500,600	1.94				
	25	500,600	2.50				
	32	500,600	3.32				
	36	500,600	3.56				
	40	500,600	4.30				
	50	500,600	4.5				
	63	500,600	4.6				
	80	500,600	6				
	100	500	7.3				
	125	500	7.6				
	160	500,600	9.6				
NT0	6	500,600	1.03	0.2	Sist 160	160	0.32
	10	500,600	1.42				
	16	500,600	2.45				
	20	500,600	236				
	25	500,600	2.7				
	32	500,600	3.74				
	36	500,600	4.3				
	40	500,600	4.7				
	50	500,600	5.5				
	63	500,600	6.9				
	80	500,600	7.6				
	100	500,600	8.9				
	125	500	10.1				
NT1	160	500	15.2	0.36	Sist 201	250	0.8
	80	500,600	6.2				
	100	500,600	7.5				
	125	500,600	10.2				
	160	500,600	13				
	200	500,600	15.2				
	224	500	16.8				
NT2	250	500	18.3	0.65	Sist 401	400	1.2
	125	500,600	9				
	160	500,600	11.5				
	200	500,600	15				
	224	500,600	16.6				
	250	500,600	18.4				
	300	500,600	21				
	315	500,600	19.2				
	355	500,600	24.5				
NT3	400	500,600	26	0.85	Sist 601	630	1.5
	315	500,600	21.7				
	355	500,600	22.7				
	400	500,600	26.8				
	425	500,600	28.9				
	500	500	32				
NT4	630	500	40.3	1.95	Sist 1001	1000	3.45
	800	380	62				
	1000	380	75				