

RL6 Fuse



1. Specifications

Type	RL-16ND	RL6-25	RL6-63
Rated voltage	500V	500V	500V
Rated current of fuse	25A	25A	63A
Rated current of fusant	1,2,4,6,10A	2,4,6,10,16,20,25A	35,50,63A
Rated breaking current	50kA cosφ=0.1-0.2	50kA cosφ=0.1-0.2	50kA cosφ=0.1~0.2
Overall dimensions	35X35X70mm	66X43X80mm	89X54X82mm
Weight	0.15kg	0.20kg	0.35kg

LFH5 Bar and Fuse Type Switch-Disconnecter

1. General

LFH5 series bar and fuse type switch disconnector is applicable in the circuit of rated voltage AC 660V and below, rated current AC160A-630A, rated frequency of 50/60Hz.

2. Specifications

Rated thermal current		160A	250A	400A	630A
Rated insulation voltage		8000V			
	380V AC20	160A	250A	400A	630A
	380V AC21	160A	250A	400A	630A
	380V AC22	160A	250A	400A	630A
	660V AC20	160A	250A	400A	630A
	660V AC21	100A	200A	315A	425A
	660V AC22	100A	160A	315A	315A
	Matched fuse	NT00	NT1	NT2	NT3
	380V Rated current of fuse (Breaking capacity)	20、25、32、35 40、50、63、80 100、125、160 (≥100kA)	80、100、125 160、200 224、250 (≥100kA)	125、160、200 224、250、300 315、355、400 (≥100kA)	315、355、400 425、500、630 (≥100kA)
	660V Rated current of fuse (Breaking capacity)	20、25、32、35 40、50、63、80 100(≥50kA)	80、100、125 160、200 (≥50kA)	123、160、200 224、250、300 315(≥50kA)	315、355 400、425 (≥50kA)